



## Perfect Synergy

The combination of optimum image quality and simplicity makes Array's 2908 Mammo Pro the premiere and logical choice for scanning prior mammograms.

Designed as an all-in-one fully self-contained tabletop digitization system, 2908 Mammo Pro is the ideal companion to full field digital mammography systems.



2908 Mammo Pro

# 2908 Mammo Pro



## Advancing the Art

2908 Mammo Pro is the first of its kind, yet it was built upon the same engineering principals that has established Array as the world leader in scanning technologies.

## Fingertip Control

2908 Mammo Pro features an integrated LCD touchscreen and autofeeder that allows total control without sacrifice to your workflow.

## Hanging Protocols

DICOM attributes are user selectable and can be applied to each scanned image, thus ensuring correct anatomic positioning while radiologists remain productive.

## Specifications:

<b>Model number</b>	<b>2908 Mammo Pro</b>
<b>Light Source</b>	<b>Solid State Laser, 600 nm</b>
<b>Sensor</b>	<b>Photomultiplier</b>
<b>Optical Density Range</b>	<b>0.0 - 4.4 OD</b>
<b>Pixel Depth</b>	<b>4096</b>
<b>Bit Depth</b>	<b>12 Bits</b>
<b>Sampling Pitch</b>	<b>50 µm</b>
<b>Optical Resolution</b>	<b>50 µm</b>
<b>Feed Capacity</b>	<b>Batch load upto 100 films</b>
<b>Scan speed</b>	<b>30 seconds at 50 µm, 18X24cm</b>
<b>Film Sizes</b>	<b>18 X 24cm, 24 X 30cm</b>
<b>Interfaces</b>	<b>USB, Internal PC, 17" LCD</b>
<b>Operating System</b>	<b>Windows XP Embedded</b>
<b>Network</b>	<b>DICOM</b>
<b>Dimensions</b>	<b>45 X 65 X 41cm</b>
<b>Weight</b>	<b>68.9 Kg</b>
<b>Power</b>	<b>100 - 120 VAC, 200 - 240 VAC</b>
<b>Options</b>	<b>Mouse, Keyboard</b>

\*Specification subject to change without notice



 **Array Corporation**

Array Corporation Europe  
www.arrayeurope.com

Array Corporation Japan  
www.array.co.jp

Array Corporation USA  
www.arrayusa.com